

SHACMAN L3000 GARBAGE TRUCK



Transport type	Waste Transportat			
Logistics type	Urban wastes			
Distance(km)	≤50	≤50		
Road type	Station / warehouse / Wharf / construction site / suburb	Station / warehouse / Wharf / construction site / suburb		
Drive	4×2	4×2		
Max weight(t)	≤25	≤18	≤25	
Crusing speed/Max speed(km/h)	80	100	80	
Loaded speed(km/h)	45~60	60~75	45~60	
Vehicle model	SX5188ZYS8N501	SX5185ZYS8J361	SX5185ZYS8N401	
Engine	WP6.220E50	WP6.210E32	WP6.210E32	
Emission standard	Euro V	Euro II	Euro II	
Displacement	6.75L	6.23L	6.23L	
Rated Output	162kW	155kW	155kW	
Max. torque	850N·m	750N·m	750N·m	
Transmission	8JS85TE-C+QD40J	8JS85TE-C+QD40J	8JS85TE-C+QD40J	
Clutch	430	430	430	
Frame	850×300(8+5)	870×270(7+4)	850×300(8+5)	
Front axle	MAN 7.5T	4.8T (Disc brake)	MAN 7.5T	
Rear axle	13T MAN double reduction 5.262	10T single reduction axle 5.125	13T MAN double reduction 4.769	
Tire	12.00R20	10.00R20	12.00R20	
Front Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs	
Rear Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs	
Fuel	Diesel	Diesel	Diesel	
Capacity of the fuel tank	200L	200L	200L	
Battery	165Ah	135Ah	165Ah	
Volume(m ³)	16	10	12	
After the suspension	1200	1100	1200	
Wheelbase	5000	3600	4000	
Max.gradeability(%)	28	44	28	
Cab	Type	L3000(upgrade)cab		
	Equipments	<ul style="list-style-type: none"> ◆ Hydraulic main seat ◆ Hydraulic suspension of cab ◆ Manual flip ◆ Electric window lifter ◆ Electric air conditioning 	<ul style="list-style-type: none"> ◆ Electric air conditioning ◆ LED daytime running light ◆ Central locking (double remote control) ◆ Front fixed rear hydraulic shock absorber ◆ Electric window lifter 	<ul style="list-style-type: none"> ◆ Hydraulic main seat ◆ Hydraulic suspension of cab ◆ Manual flip ◆ Electric window lifter ◆ Electric air conditioning
Vehicle	Optional	<ul style="list-style-type: none"> ● Airbag main seat 	<ul style="list-style-type: none"> ● Deflector ● Airbag main seat 	<ul style="list-style-type: none"> ● Airbag main seat