

SHACMAN L3000 LORRY TRUCK



Transport type	Standard load transport		
Logistics type	Daily use and food/agricultural and sideline products		
Distance(km)	≤200km		
Road type	Urban / National Road		
Drive	4×2		
Max weight(t)	12~18		
Crusing speed/Max speed(km/h)	90	90	90
Loaded speed(km/h)	55~65	45~65	55~65
Vehicle model	SX11858K571	SX11888K501	SX11858J501C
Engine	WP6.240E32	WP6.245E50	ISDe210 30
Emission standard	Euro II	EuroV	Euro III
Displacement	6.23L	6.75L	6.7L
Rated Output	186kW	180kW	155kW
Max. torque	/	900N·m	800N·m
Transmission	8JS85TE-C	8JS85TE-C	8JS85TE-C
Clutch	395	395	395
Frame	870×250(7+4)	870×250(7+4)	870×250(7+4)
Front axle	4.8T (Disc brake)	4.8T (Disc brake)	4.8T (Disc brake)
Rear axle	10T single reduction 4.625	10T single reduction 4.625	10T single reduction 4.625
Tire	10.00R20	10.00R20	10.00R20
Front Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs
Rear Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs
Fuel	Diesel	Diesel	Diesel
Capacity of the fuel tank	200L	200L	200L
Battery	135Ah	135Ah	135Ah
Trunk(L×W×H)	7750×2450×600	6750×2450×600	6750×2450×600
Wheelbase	5700	5000	5000
After the suspension	2600	2300	2300
Max.gradeability(%)	45	45	45
	Type	L3000 Cab	
Cab	Equipments	<ul style="list-style-type: none"> ◆ Electric air conditioning ◆ Electric window lifter ◆ LED daytime running light ◆ Central locking (double remote control) ◆ Front fixed rear hydraulic shock absorber 	
Vehicle	Optional	<ul style="list-style-type: none"> ● Deflector ● Air main seat ● Electric flip 	