

SHACMAN X3000

LORRY TRUCK



Transport type	Complex transport		
Logistics type	Daily industrial products and food		
Distance (km)	≤300km		
Road type	Paved roads		
Drive	6x4	8x4	8x4
Max weight(t)	≤35	≤50	≤50
Crusing speed/Max speed(km/h)	90	90	90
Loaded speed(km/h)	50~65	50~65	50~65
Vehicle model	SX1255R434	SX13155U456	SX13155T456C
Engine	WP10.340E22	WP12.400E201	ISME385 30
Emission standard	Euro II	EuroII	EuroIII
Displacement	9.726L	11.596L	10.8L
Rated Output	250kW	294kW	283kW
Max. torque	1400N.m	1800N.m	1835N.m
Transmission	10JSD180	12JSD200T-B	12JSD200T-B
Clutch	430	430	430
Frame	850x300 (8+5)	850x300 (8+5)	850x300(8+5)

Front axle	MAN 7.5T	MAN 7.5T	MAN 7.5T
Rear axle	13T MAN double reduction 4.769	13T MAN double reduction 4.266	5 13T MAN double reduction 4.769
Tire	12.00R20	12.00R20	12.00R20
Front Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs
Rear Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs
Fuel	Diesel	Diesel	Diesel
Capacity of the fuel tank	400L (Aluminum shell)	400L (Aluminum shell)	400L (Aluminum shell)
Battery	180Ah	180Ah	180Ah
Dimensions(LxWxH)	9700x2490x3250	11600x2490x3250	11600x2490x3250
Trunk(LxWxH)	7500x2300x800	9500x2300x800	9500x2300x800
Wheelbase	4375+1400	1800+4575+1400	1800+4575+1400
After the suspension	2400	2300	2300
Approach/Departure angle (°)	18/12	18/12	18/12
Max.gradeability(%)	34	34	34
Cab	Try	X3000 , mid-lengthened flat roof	
	Equipments	<ul style="list-style-type: none"> ◆Rear window◆Manual sunroof ◆Hydraulic driver seat with seatbelts ◆Hydraulic suspension of cab ◆Electronic air conditioning with temperature control ◆Electric window◆Radio with MP3 player 	
	Optional	<ul style="list-style-type: none"> ●Central locking●Air suspended main seat ●Front lamp protector●Four point air suspended cabin ●Desert air filter●Oil type air filter ●Electric cab turning ●11.00R20 	